

# H-LINK

## MILLIMETER-WAVE RADIO SIGNALS, HIGH-DATA THROUGH PLASTIC MEDIA

### + WHAT IS H-LINK?

H-Link is the first system that guides radio waves both in the air and through a flexible plastic tube. This low-cost hybrid technology allows the transmitter to perform 360° rotations, avoiding cable kinking. Initially designed for robotics, H-Link ensures broadband in confined areas (eg. glove boxes).

H-Link can transfer information over distances up to ten meters at a speed of 15 Gbits/s. With an average data transmission speed of 6 Gbits/s over a little more than two meters, the system can transfer a 4K video, eliminating the data compression/decompression.

### + APPLICATIONS

- H-link has been designed for **robotics**, enabling high data rate communication to perform:
  - Remote chemistry in confined volume
  - Remote biology in glove box: viruses and bacteria
  - Remote micro-nano technology development
  - Remote nuclear material manipulation, etc.
- H-link can also be used for **e-health**, such as remote medical visits/check-up, and surgical intervention (dentistry).

## + WHAT'S NEW?

H-link offers significant advantages over copper and fiber optic cable:

- It uses a tenth of the energy required to transmit a signal
- It is less sensitive to vibration and electromagnetic waves
- Because the system uses millimeter waves rather than nanometer waves (optical fiber), it does not need to be heat spliced or welded—it can be connected by hand with a piece of tape
- Plastic is much lighter in weight than copper

H-Link's emitter transform digital SDI in mmW modulated signal. The signal is radiated through either a plastic wave guide or an antenna free space link to the receiver which delivers digital SDI. In terms of technical performance, H-Link offers:

- Full duplex, multi channels.
- No additional conversion (vs. optics), no equalization (vs. copper)
- No micron-level alignment (vs. optic), no electrical contact (vs. copper)
- Low loss versus copper and wireless
- High energy efficiency (around 1pJ/bit/m)
- Freedom of movement including tilt, angle and misalignment

## + WHAT'S NEXT?

CEA-Leti is currently working towards the development of customer ad-hoc solution using STMicroelectronics' 60ghz transceiver and Radiall's antenna horn interface.

The team is improving the interface and developing a multi-channels transceiver within the 100-150 GHz band. They also try to enhance the plastic coupling structures.

## KEY FACTS

- A 12Gbs 64QAM and OFDM compatible Millimeter-Wave Communication Link Using Plastic Waveguide Design, F.Voineau, C.De hos, B.Martineau, M.Sié, M.Perchicot, H.Nguyen, A.Ghiotto and E.Kerhervé; 2018 IEEE Radio and Wireless Symposium (RWS) Anaheim CA 2018, pp250-252
- Patents: 3 STMicroelectronics; 4 CEA-Leti; 1 IMS.



## INTERESTED IN THIS TECHNOLOGY?

Contact:

**Didier Belot**

[didier.belot@cea.fr](mailto:didier.belot@cea.fr)

+33 608 751 309

CEA-Leti, technology research institute

Commissariat à l'énergie atomique et aux énergies alternatives  
Minatec Campus | 17 avenue des Martyrs | 38054 Grenoble Cedex 9 | France

[www.leti-cea.com](http://www.leti-cea.com)



@CEA\_Leti



CEALeti



CEA-Leti

