## FOCUS A

# The different types of magnetism

he origins of magnetism lie in the properties of **electrons** as explained by the laws of **quantum physics**. Part of an electron's magnetic properties (spin magnetism) results from its quantummechanical **spin** state, while another part results from the orbital motion of electrons around an atom's nucleus (orbital magnetism) and from the magnetism of the nucleus itself (nuclear magnetism). This is put to use, in particular, for nuclear magnetic resonance imaging in the medical field. Magnetism is therefore produced by electric charges in motion. The force acting on these charges, called the Lorentz force, demonstrates the presence of a magnetic field.

Electrons have an intrinsic magnetic dipole moment (the magnetic quantum state being the Bohr magneton), which can be pictured as an electron's rotational motion of spin around itself in one direction or another, oriented either upwards or downwards. The spin quantum number (one of the four numbers that 'quantifies' the properties of an electron) equals 1/2 (+ 1/2 or - 1/2). A pair of electrons can only occupy the same orbital if they have opposite magnetic dipole moments.


Each atom acts like a tiny magnet carrying an intrinsic magnetic dipole moment. A nucleus (the **neutron** and **proton** individually have a half-integer spin) will have a half-integer spin if it has an odd atomic mass number; zero spin if the **atomic mass number** and charge are even, and an integer spin if the atomic mass number is even and the charge odd.

On a larger scale, several magnetic moments can together form magnetic

domains in which all these moments are aligned in the same direction. These spatial regions are separated by domain walls. When grouped together, these domains can themselves form a macroscopic-scale magnet (Figure E1).


The type of magnetism that comes into play is determined by how these elementary constituents are ordered, and is generally associated with three main categories of material: *ferromagnetic*, *paramagnetic* and *diamagnetic*.

Any material that is not diamagnetic is by definition paramagnetic provided that its magnetic susceptibility is positive. However, ferromagnetic materials have particularly high magnetic susceptibility and therefore form a separate category. 1. Ferromagnetic materials are formed of tiny domains inside which atoms exhibiting parallel magnetisation tend to align themselves in the direction of an external magnetic field like elementary dipoles. In fact, the magnetic moments of each atom can align themselves spontaneously within these domains, even in the absence of an external magnetic field. Applying an external field triggers domain wall movement that tends to strengthen the applied field. If this field exceeds a certain value, the domain most closely oriented with the direction of the applied field will tend to grow at the expense of the other domains, eventually occupying the material's whole volume. If the field diminishes, the domain walls will move, but not symmetrically as the walls cannot fully reverse back to their original positions. This results in remanent magnetisation, which is an important feature of naturally occurring magnetite, or of magnets themselves.



#### Figure E1.

Intrinsic magnetic dipole moments have parallel alignment in ferromagnetic materials (a), anti-parallel alignment but zero magnetisation in antiferromagnetic materials (b), and anti-parallel alignment with unequal moments in ferrimagnetic materials (c).



#### Figure E2.

The induction B of a magnetic material by a coil is not proportional to its magnetic excitation (*field H*). While the initial magnetisation forms an 0sS-type curve, shown in blue in the figure, it reaches saturation at point s. Only a partial induction is retained if the field approaches zero; this remanent induction can only be cancelled out by reversing the magnetic field to a "coercive" field value. This hysteresis loop illustrates the losses due to "friction" between the magnetic domains shown on the area bounded by the magnetisation and demagnetisation curves.

The whole process forms a hysteresis loop, i.e. when the induced field is plotted against the applied field it traces out a hysteresis curve or loop where the surface area represents the amount of energy lost during the irreversible part of the process (Figure E2). In order to cancel out the induced field, a coercive field has to be applied: the materials used to make artificial permanent magnets have a high coercivity.

Ferromagnetic materials generally have a zero total magnetic moment as the domains are all oriented in different directions. This ferromagnetism disappears above a certain temperature, which is known as the Curie Temperature or Curie point.

The magnetic properties of a given material stem from the way the electrons in the metallic cores of a material or of a **transition metal** complex collectively couple their spins as this results in all their spin moments being aligned in the same direction.

Materials whose atoms are widely distributed throughout their **crystal** structure tend to better align these elementary magnets via a coupling effect. This category of materials, which is characterised by a very high positive magnetic



A Transrapid train using magnetic levitation arriving at the Long Yang bus station in Shanghai (China). This German-built high-speed, monorail train was commissioned in 2004 to service the rail link to Pudong international airport.

susceptibility, includes iron, cobalt and nickel and their alloys, steels in particular, and some of their compounds, and, to a lesser extent, some rare earth metals and alloys with large crystal lattices, and certain combinations of elements that do not themselves belong to this category. In ferrimagnetic materials, the magnetic domains group into an anti-parallel alignment but retain a non-zero magnetic moment even in the absence of an external field. Examples include magnetite, ilmenite and iron oxides. Ferrimagnetism is a feature of materials containing two types of atoms that behave as tiny magnets with magnetic moments of unequal magnitude and anti-parallel alignment. Antiferromagnetism occurs when the sum of a material's parallel and anti-parallel moments is zero (e.g. chromium or haematite). In fact, when atoms are in a close configuration, the most stable magnetic arrangement is an anti-parallel alignment as each magnet balances out its neighbour so to speak (Figure E1).


2. Paramagnetic materials behave in a similar way to ferromagnetic materials, although to a far lesser degree (they have a positive but very weak magnetic susceptibility of around 10-3). Each atom in a paramagnetic material has a non-zero magnetic moment. In the presence of an external magnetic field, the magnetic moments align up, thus amplifying this field. However, this effect decreases as temperature rises since the thermal agitation disrupts the alignment of the elementary dipoles. Paramagnetic materials lose their magnetisation as soon as they are released from the magnetic field. Most metals, including alloys comprising ferromagnetic elements are paramagnetic, as

are certain minerals such as pegmatite. 3. Diamagnetic materials exhibit a negative and an extremely weak magnetic susceptibility of around 10-5. The magnetisation induced by a magnetic field acts in the opposite direction to this field and tends to head away from field lines towards areas of lower field strengths. A perfect diamagnetic material would offer maximum resistance to an external magnetic field and exhibit zero permeability. Metals such as silver, gold, copper, mercury or lead, plus quartz, graphite, the noble gases and the majority of organic compounds are all diamagnetic materials.

In fact, all materials exhibit diamagnetic properties to a greater or lesser extent, resulting from changes in the orbital motion of electrons around atoms in response to an external magnetic field, an effect that disappears once the external field is removed. As Michael Faraday showed all that time ago, all substances can be "magnetised" to a greater or lesser degree provided that they are placed within a sufficiently intense magnetic field.

### Electromagnetism

It was the Danish physicist Hans Christian Ørsted, professor at the University of Copenhagen, who, in 1820, was first to discover the relationship between the hitherto separate fields of electricity and magnetism. Ørsted showed that a compass needle was deflected when an electric current passed through a wire, before Faraday had formulated the physical law that carries his name: the magnetic field produced is proportional to the intensity of the current. Magnetostatics is the study of static magnetic fields, i.e. fields which do not vary with time.



Close-up of the magnets used to guide and power the train.

Magnetic and electric fields together form the two components of **electromagnetism**. Electromagnetic waves can move freely through space, and also through most materials at pretty much every frequency band (radio waves, microwaves, infrared, visible light, ultraviolet light, X-rays and gamma rays). Electromagnetic fields therefore combine electric and magnetic **force** fields that may be natural (the Earth's magnetic field) or man-made (low frequencies such as electric power transmission lines and cables, or higher frequencies such as radio waves (including cell phones) or television.

Mathematically speaking, the basic laws of electromagnetism can be summarised in the four Maxwell equations (or Maxwell-Lorentz equations) which can be used to provide a coherent description of all electromagnetic phenomena from electrostatics and magnetostatics to electromagnetic wave propagation. James Clerk Maxwell set out these laws in 1873, thirty-two years before Albert Einstein incorporated the theory of electromagnetism in his special theory of relativity, which explained the incompatibilities with the laws of classical physics.